QWISE-FM-SBJSGC-2019-LXH Company Standard

Hunan WISE New Material Technology Co., Ltd.

Powder sub-factory Powder product production process equipment safety technical regulations

Spiral mixer safety technical regulations

Approved by: Zhaohui LIU Prepared by: Liyun Yun Xing Wang
Checked by Technical Dept: Yizhong Zhang and Yongshen Gong
Checked by Sub-Factory: Zhengchen Xu and Zhengdao Xiao
August 1, 2019 Release August 1, 2019 Effective

Hunan WISE New Material Technology Co., Ltd. Release

QWISE-FM-SBJSGC-2019-LXH Company Standard

Hunan WISE New Material Technology Co., Ltd.

Powder sub-factory

production process equipment safety technical regulations Spiral mixer safety technical regulations

- 1. Wear overalls, work shoes, work caps, dust masks, and canvas gloves before work.
- 2. Check the inside and outside of the cylinder, whether the motor and the rotating part are normal, and whether the pulley guard is intact.
- 3. When loading, first open the outer cover and inner cover, and place the hopper in the loading port. After the filling is completed, the inner and outer covers must be fixed.
- 4. Start the cylinder and the propeller; observe the normal operation before leaving.
- 5. When unloading, first stop the motor. When it stops running, remove the inner cover, close the outer cover, start the motor to unload, and hit the mixer outer cylinder with a wooden hammer so that the material stuck on the cylinder enters the drum.
- 6. If abnormal sound or card machine phenomenon occurs during the operation of the mixer, stop it immediately.
- 7. After the operation is completed, the operation table and equipment should be cleaned

Approved by: Zhaohui LIU Prepared by: Liyun Yun Xing Wang
Checked by Technical Dept: Yizhong Zhang and Yongshen Gong
Checked by Sub-Factory: Zhengchen Xu and Zhengdao Xiao
August 1, 2019 Release August 1, 2019 Effective

Hunan WISE New Material Technology Co., Ltd. Release